

# STANDARD FEATURES

#### Floor Models see page 8

see price list for flooring options

## Sidewall Height

8' sidewalls

#### Roof

12 pitch roofAluminum dripedge30 year dimensional shingles6' overhang

## Construction

Strongback Nailer Primed Smartside Siding 2x4" wall framing 2x4" double top-plate Air vents Wall studs 16" o.c. 6" fascia trim Synthetic felt paper Truss anchor screws

#### Doors

Entrance door with glass

## Lofts

. . . . . . . . . . . .

Full loft with steps, landing, and railing Loft below top plate 2x10" loft joists 16" o.c. 16' wide buildings 14" floor trusses 24" o.c. 20' wide buildings 16" floor trusses 24" o.c. 24' wide buildings

. . . . . . . . . . .

## Decks

6' deck and 'Y' posts are standard on 16' wide cabins

6' deck and posts are optional on 20' and 24' wide cabins

## BUILDING SIZES ······

WIDTH		DEPTH						HEIGHT
		20'	24'	28'	32'	36'	40'	199
1	16'	٠	•	•	•		10	17' 7"
1	20'		•	•	•	•	•	19' 9"
	24'		•	•	•	•	•	21' 9"

# POPULAR OPTIONS

Vinyl insulated windows Ridgevent and vented soffit Additional doors

